

## ACCESSORIES - ZUBEHÖR

### Water Flow Regulator Wasserbatterin

#### Main Technical Features

- Tube made of polyamide (satandart)
- Bodies made of PA 6 wit 30% fibergals
- Regulating taps in brass
- Thermameter (satandad)
- Vitrilic rubber or-rings in vitrilo (hardness 70 SHA)
- Brass intel and outlet valves are inserted in the body 3/8"
- Maximum working temperature 90° C

#### Technische Spezifikationen

- Poliamisiertes Rohr (Standard)
- Körper mit PA 6 30% Fiberglas
- Der Regler ist Messing.
- Thermometer (Standard)
- Vityril Gummi O-Ringe (Härte 70 S-HA)
- Messing-Einlass- und Auslassventile sind in 3/8"
- Abmessungen am Körper angebracht.
- Max. Arbeitstemperatur 90°C



| Order No / Bestellnr. |             | No of Entrance | A   |
|-----------------------|-------------|----------------|-----|
| Male Type             | Female Type |                |     |
| TFW 01-DU             | TFW 01 - EU | 1              | 73  |
| TFW 02-DU             | TFW 02 - EU | 2              | 126 |
| TFW 03-DU             | TFW 03 - EU | 3              | 129 |
| TFW 04-DU             | TFW 04 - EU | 4              | 231 |
| TFW 05-DU             | TFW 05 - EU | 5              | 284 |
| TFW 06-DU             | TFW 06 - EU | 6              | 339 |
| TFW 07-DU             | TFW 07 - EU | 7              | 392 |
| TFW 08-DU             | TFW 08 - EU | 8              | 444 |
| TFW 09-DU             | TFW 09 - EU | 9              | 497 |
| TFW 10-DU             | TFW 10 - EU | 10             | 552 |
| TFW 11-DU             | TFW 11 - EU | 11             | 607 |
| TFW 12-DU             | TFW 12 - EU | 12             | 659 |

